



## Technical Datasheet

PRODUCT CODE	CM AP 200
PRODUCT DESCRIPTION	ARAMID FABRIC - 1580 Dtex 200 gr/m2 Plain

LAYER	REINFORCEMENT CONSTRUCTION
WARP PER END	6.1 / Warp - 1580 Dtex ARAMID FIBER
WEFT PER END	6.1 / Weft - 1580 Dtex ARAMID FIBER

### FIBER PROPERTIES



YARN	1580 Dtex 1000F High Tenacity / KOLON - HERACRON ARAMID
TENSILE STRENGTH	ARAMID: 197 cN/tex
TENSILE MODULUS	ARAMID: 118 GPa
STRAIN	ARAMID: 2.5%
RESIN COMPATIBILITY	POLYESTER,VINYLESTER,EPOXY RESINS
TEST METHOD	ISO 10618

### ROLL INFO

ROLL WEIGHT	20 KG
ROLL LENGTH	100 MT
ROLL WIDTH	100 CM

PACKAGING	ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES
-----------	---

STORAGE	STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT.
---------	---

<b>CERTIFICATION</b>  	CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2008 QA SYSTEM
--	--