



Technical Datasheet

PRODUCT CODE	CM AP 475
PRODUCT DESCRIPTION	ARAMID FABRIC - 3360 Dtex 475 gr/m2 Plain

LAYER	REINFORCEMENT CONSTRUCTION
WARP PER END	7.0 / Warp - 3360 Dtex ARAMID FIBER
WEFT PER END	7.0 / Weft - 3360 Dtex ARAMID FIBER

FIBER PROPERTIES



YARN	ARAMID 3360 Dtex
TENSILE STRENGTH	ARAMID: 203 cN/tex
TENSILE MODULUS	ARAMID: 83 GPA
STRAIN	ARAMID: 3,6%
RESIN COMPATIBILITY	POLYESTER,VINYLESTER,EPOXY RESINS
TEST METHOD	ISO 10618

ROLL INFO

ROLL WEIGHT	47.5 KG
ROLL LENGTH	100 MT
ROLL WIDTH	100 CM

PACKAGING	ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES
-----------	---

STORAGE	STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT.
---------	---

CERTIFICATION  	CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2008 QA SYSTEM
--	--