



Technical Datasheet

PRODUCT CODE	CM AP 613 Ballistic Aramid
PRODUCT DESCRIPTION	ARAMID FABRIC - 550 Dtex 135 gr/m2 Plain

LAYER	REINFORCEMENT CONSTRUCTION
WARP PER END	12.3 / Warp - 550 Dtex ARAMID FIBER
WEFT PER END	12.3 / Weft - 550 Dtex ARAMID FIBER

FIBER PROPERTIES



YARN	ARAMID 550 Dtex 1000F Type 2040 Ballistic Fiber
TENSILE STRENGTH	ARAMID: 135 cN/tex
TENSILE MODULUS	ARAMID: 91 GPA
STRAIN	ARAMID: 3.45%
RESIN COMPATIBILITY	POLYESTER,VINYLESTER,EPOXY RESINS
TEST METHOD	ISO 10618

ROLL INFO

ROLL WEIGHT	17.5 KG
ROLL LENGTH	100 MT
ROLL WIDTH	130 CM

PACKAGING	ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES
-----------	---

STORAGE	STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT.
---------	---

CERTIFICATION  	CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2008 QA SYSTEM
---	--