



## Technical Datasheet

PRODUCT CODE	CM CT4 300
PRODUCT DESCRIPTION	CARBON FABRIC - 6K 300 gr/m2 4/4 TWILL

LAYER	REINFORCEMENT CONSTRUCTION
WARP PER END	3.7 / Warp - 400 Tex 6K CARBON FIBER
WEFT PER END	3.7 / Weft - 400 Tex 6K CARBON FIBER

### FIBER PROPERTIES



YARN	CARBON FIBER A/38 - 6K
TENSILE STRENGTH	CARBON: 3800 MPA
TENSILE MODULUS	CARBON: 240 GPA
STRAIN	CARBON: 1.6%
RESIN COMPATIBILITY	POLYESTER,VINYLESTER,EPOXY RESINS
TEST METHOD	ISO 10618

### ROLL INFO

ROLL WEIGHT	30 KG
ROLL LENGTH	100 MT
ROLL WIDTH	100 CM

PACKAGING	ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES
-----------	---

STORAGE	STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT.
---------	---

<b>CERTIFICATION</b>  	CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2008 QA SYSTEM
--	--